



6210 Bearing 2D drawings and 3D CAD models

**High Quality & Amazing Price Ball Bearing 6210  
6211 SKF NSK NTN NACHI Vehicle Used**

Bearing No. 6210

Size	50x90x20 mm
Bore Diameter	50 mm
Outer Diameter	90 mm
Width	20 mm
d	50 mm
D	90 mm
B	20 mm
C	20 mm
r min.	1.1 mm
da min.	57 mm
Da max.	83 mm
ra max.	1.0 mm
Weight	0.463 Kg
Basic dynamic load rating (C)	35 kN
Basic static load rating (C0)	23,2 kN
(Grease) Lubrication Speed	7000 r/min
Category	Single Row Ball Bearings
Inventory	0.0
Manufacturer Name	NACHI
Minimum Buy Quantity	N/A
Weight / Kilogram	0
EAN	4991893721850
Product Group	B00308
Enclosure	Open
Precision Class	ABEC 1   ISO P0



## China abec 7 Bearings Supplier

Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Internal Clearance	C0-Medium
Inch - Metric	Metric
Long Description	50MM Bore; 90MM Outside Diameter; 20MM Outer Race Width; Open; Ball Bearing; ABEC 1   ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features; C0-Medium Internal Clearance; Steel Cage
Other Features	Deep Groove
Category	Single Row Ball Bearing
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Manufacturer URL	<a href="http://www.nachiamerica.com">http://www.nachiamerica.com</a>
Weight / LBS	1.0229
Inner Race Width	0 Inch   0 Millimeter
Outer Race Width	0.787 Inch   20 Millimeter
Outside Diameter	3.543 Inch   90 Millimeter
Bore	1.969 Inch   50 Millimeter
Bore Type	Cylindrical Bore
Configuration	Single Row
Bore Size	50 mm
Width	20 mm
Fillet Radius/Chamfer	1.1 mm



## China abec 7 Bearings Supplier

Dynamic Load Rating	35,000 N
Static Load Rating	23,200 N
Limiting Speed - Grease	7,100 rpm
Limiting Speed - Oil	8,600 rpm
Factor fo	14.4
Radial Clearance	0.006 to 0.023 mm
da (min)	57 mm
Da (max)	83 mm
ra (max)	1 mm